

**Declaration of Performances/Regulation EU 305/2011 Annex III**

Dop No. 1607040

**1) Unique identification code of the product-type**

Light transmitting flat multiwall polycarbonate sheet  
AKYVER® SUN TYPE 16-7W BRONZE

**2) Intended use or uses of construction product, in accordance with the applicable harmonized technical specification**

For roofing and cladding of buildings and/or 'internal and external use for walls and ceilings

**3) Manufacturer**

Corplex France Kaysersberg  
75 Route de Lapoutroie  
68240 Kaysersberg, France

T +33 (0)3 89 78 32 51  
F +33 (0)3 89 78 38 56  
www.corplex.com

**4) Authorised representative**

Non applicable

**5) System or systems of assessment and verification of constancy of performances of the construction product**

System 3

**6) In case of the declaration of performance concerning a construction product covered by a harmonized standard**

Non applicable

**7) Declared performances**



68240

|   |  |                |
|---|--|----------------|
| <b>External fire performance</b>                  | $F_{\text{roof}}$  | EN 16153: 2015 |
| <b>Reaction to fire</b>                           | B s1 d0  |                |
| <b>Resistance to fire</b>                         | NPD  |                |
| <b>Water vapour permeability</b>                  | $3,8 \times 10^{-5} \text{ mg/m h Pa}$   |                |
| <b>Water/ air permeability</b>                    | Pass   |                |
| <b>Release of dangerous substances</b>            | NPD  |                |
| <b>Dimensional tolerances</b>                     | Pass   |                |
| <b>Shatter properties (save breakability) as:</b> |  |                |
| - Small hard body impact resistance               | Pass   |                |
| - Large soft body impact resistance               | NPD  |                |
| Mechanical resistance<br>(deformation behaviour)  | Bx= 195.3 Nm <sup>2</sup> /m<br>By= 91.1 Nm <sup>2</sup> /m<br>Sy= 2777 N/m<br>Mb= 70.1 Nm/m |                |
| <b>Direct airborne sound insulation</b>           | NPD  |                |
| <b>Thermal transmittance</b>                      | NPD  |                |
| <b>Light transmittance</b>                        | NPD  |                |
| <b>Total solar energy transmittance</b>           | NPD  |                |
| <b>Resistance to fixings</b>                      | Fixing method (see the manufacturer's informations)  |                |
| <b>Durability, as variation (after ageing)</b>    |  |                |
| - Of yellowness index                             | ΔA   |                |
| - Of light transmittance                          | ΔA   |                |
| - Of deformation flexural modulus                 | Cu 0   |                |
| - Of tensile strength                             | Ku 0   |                |

**8) The performances of the product identified in point 1 are in conformity with the declared performances in point 7. This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 3.**

**Signed for and on behalf of the manufacturer by:**

Name : GOEPFERT Felix

Function : Technical manager AKYVER®

Place and date of issue : Kaysersberg, 07<sup>th</sup> September 2020

Signature :

